

DM500™

The DM500™ mailing system delivers new levels of simplicity and productivity by feeding, sealing and imprinting postage at up to 135 letters per minute.

Automatic mail processing

- > Rapidly processes up to 135 letters per minute.
- > Self-aligning feed system lets you continually add mail during processing maximizing total throughput.
- > The wide feed deck allows for easy processing of oversized envelopes up to 10" x 13".
- > Thoroughly seals every mail piece tip-to-tip ensuring that your important business communications are secure.
- > Integrated weighing option is simple to use and ensures the right amount of postage on every mail piece.
- > Easy-to-use and easy-to-read display enhances operation by clearly indicating if you're low on postage or ink, and the operator definable postage lock out feature will even prevent the accidental application of too much postage.
- > Conveniently uses self-adhesive roll tape to easily handle thick envelopes, flats, parcels and tubes.



Advanced mailing technology

- > IntelliLink™ Control Centre saves time by putting operations – weighing and rating, adding postage funds and updating postal rates – all in one convenient place.
- > The new digital technology meets Canada Post Corporation's standards and provides the flexibility for future enhancements.
- > Eliminates trips to the Post Office – a single key stroke allows you to get all the postage you need from our Postage By Phone™ system. You'll have full access to Canada Post's services via the IntelliLink™ Control Centre including rates for domestic and international letters and parcels, all without ever having to leave your office.
- > Advanced accounting packages available to help control mailroom expenses.

Specifications

Document Throughput

Speed: 135 letters per minute (lpm)

Envelopes

Minimum size: 3.5" x 5"
Maximum size: 10" x 13"
Thickness:
Minimum .007"
Maximum 5/8"
Flap depth:
Minimum 1"
Maximum 3"

Physical Dimensions:

L x D x H: (without stacker) 35" x 19" x 15" (88.9cm x 38.1cm x 48.3cm)
Weight: 64 lbs (29 kgs)

Electrical

Power requirements: 120V, 60 Hz
Approvals: ULC

Connectivity

Phone line: Standard analog
Supplied set-up kit includes: Phone line splitter and 6' (1.8m) phone cord

Options

External weigh platforms Accounting options
Scale stand for external Standard or customized messages
weigh platforms Postal rating options



Engineering the flow of communication™

Pitney Bowes Canada
5500 Explorer Drive
Mississauga, ON L4W 5C7

For more information call toll-free:
1-800-672-6937

www.pitneybowes.ca

© 2003 Pitney Bowes Inc. All rights reserved. AD950-367B1